

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representation of
The original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**


THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H01J 1/30, 31/12		A1	(11) International Publication Number: WO 00/02223
			(43) International Publication Date: 13 January 2000 (13.01.00)
(21) International Application Number: PCT/US99/14799		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 28 June 1999 (28.06.99)			
(30) Priority Data: 09/110,166 6 July 1998 (06.07.98) US			
(71) Applicant: THE REGENTS OF THE UNIVERSITY OF CALIFORNIA [US/US]; 8th floor, 1111 Franklin Street, Oakland, CA 94602-5200 (US).			
(72) Inventors: LONG, Dinh, N.; 2011 #C Olivera Road, Concord, CA 94520 (US). BALOOCH, Mehdi; 551 Colusa Avenue, Berkeley, CA 94707 (US). MC LEAN, William, II; 4206 Atlas Avenue, Oakland, CA 94619 (US). SCHILDBACH, Marcus, A.; 1363 Kathy Court, Livermore, CA 94550 (US).			
(74) Agent: GRZYBICKI, Daryl, S.; P.O. Box 808, L-703, Livermore, CA 94551 (US).		Published With international search report.	

(54) Title: JUNCTION-BASED FIELD EMISSION DISPLAY



(57) Abstract

A junction-based field emission display, wherein the junctions are formed by depositing a semiconducting or dielectric, low work function, negative electron affinity (NEA) silicon-based compound film (SBCF) onto a metal or n-type semiconductor substrate. The SBCF can be doped to become a p-type semiconductor. A small forward bias voltage is applied across the junction so that electron transport is from the substrate into the SBCF region. Upon entering into this NEA region, many electrons are released into the vacuum level above the SBCF surface and accelerated toward a positively biased phosphor screen anode, hence lighting up the phosphor screen for display. To turn off, simply switch off the applied potential across the SBCF/substrate. May be used for field emission flat panel displays.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

JUNCTION-BASED FIELD EMISSION DISPLAY

The United States Government has rights in this invention pursuant to Contract No. W-7405-ENG-48 between the United States Department of Energy and the University of California for the operation of Lawrence Livermore National Laboratory.

BACKGROUND OF THE INVENTION

The present invention relates to field emission displays, particularly to a junction-based field emission display, and more particularly to a field emission display which utilizes junctions formed by depositing a semiconducting or dielectric, low work function, negative electron affinity (NEA), silicon-based compound film (SBCF) onto a metal substrate or an n-type semiconductor substrate.

Field emission displays traditionally rely on electron emission from arrays of precisely manufactured sharp tips. The ease of electron emission, and therefore the reduction in energy consumption of the display, depends not only on the work functions of the materials used to fabricate the tips but also on the sharpness of the tips. Thus there has been a need for a field emission structure that provides a quick and inexpensive way to reduce drastically the voltages necessary to extract electrodes from

the cathodes and to remove completely the requirement of fabricating sharp tips in field emission applications.

5 The present invention provides a solution to the above-mentioned need by providing a junction-based field emission structure which eliminates the use of sharp tips, reduces the voltages necessary to extract electrons, and provides an inexpensive field emission display. The field emission display of the present invention utilizes junctions formed by depositing a semi-
10 conducting or dielectric, low work function, preferably NEA SBCF onto a metal substrate or an n-type semiconductor substrate. A small forward bias voltage is applied across the junction so that electron transport is from the substrate into the SBCF region; and upon entering into this NEA region, many electrons are released into the vacuum adjacent the junction and accelerated toward a
15 positively biased phosphor screen anode, lighting it up for display.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved field emission display.

A further object of the invention is to provide a junction-based field emission display.

20 A further object of the invention is to provide a field emission display which eliminates the use of sharp tips.

Another object of the invention is to provide a device for field emission applications which reduces the voltages necessary to extract electrons from the cathode.

25 Another object of the invention is to provide a field emission display which utilizes junctions formed by a semiconducting or dielectric, low work function, preferably NEA SBCF onto a metal or n-type semiconductor substrate.

Another object of the invention is to provide a junction-based field emission display using a silicon-based compound (SBC) deposited directly on either an n-type semiconductor or a metal substrate.

5 Another object of the invention is to provide a field emission device using an SBC, which consists of silicon, oxygen, and an alkali metal deposited on a metal or n-type semiconductor substrate.

10 Another object of the invention is to provide a junction-based field emission display wherein a small forward bias voltage is applied across the junction so that electron transport is from a substrate into an SBC causing release of electrons which are accelerated toward a positively biased phosphor screen anode.

15 Other objects and advantages of the present invention will become apparent from the following description and accompanying drawings. Broadly, the present invention is a junction-based field emission structure which provides a quick and inexpensive way to reduce drastically the voltages necessary to extract electrons from the cathode and to remove completely the requirement of fabricating
20 sharp tips in field emission applications. The junction-based field emission device uses a semiconducting or dielectric and NEA SBCF deposited directly onto either an n-type semiconductor or a metal substrate. The SBCF can be doped to become a p-type semiconductor. The SBCF consists of silicon, oxygen, and an alkali
25 metal, such as Cs or Ba, and is synthesized by the techniques of thermal vaporization and pulsed laser deposition. To light up a phosphor screen of a field emission display, such as a flat panel display, a forward bias voltage is applied across the junction so that electrons flow from the substrates into the SBCF region, and due to

the NEA property of this region, many electrons immediately escape to the vacuum level and are accelerated toward the positively biased phosphor screen anode plate to light it up for display. To turn off the screen, simply switch off the applied voltage across the junction.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The accompanying drawing, which is incorporated into and forms a part of the disclosure, illustrates an embodiment of the invention and, together with the description, serves to explain the principles of the invention.

10 Figure 1 schematically illustrates a single junction-based field emission display, in accordance with the present invention.

 Figure 2 schematically illustrates a multiple junction-based field emission display, in accordance with the invention.

DETAILED DESCRIPTION OF THE INVENTION

15 The present invention is directed to a junction-based field emission structure that provides a quick and inexpensive way to reduce drastically the voltages necessary to extract electrons from the cathodes and to remove completely the requirement of fabricating sharp tips in field emission applications. The invention involves a semiconducting or dielectric and NEA SBCF deposited directly onto either an n-type semiconductor or a metal substrate, and such has
20 been shown to have excellent stability with varying temperature and environment. The SBC consists of silicon, oxygen, and an alkali metal, such as Cs, Ba, K, Rb, and Li, and is synthesized by the known techniques of thermal vaporization and pulsed laser deposition. The as-deposited SBC film (SBCF) region has an
25 abundance of surface states in the band gap and may also be optionally doped to become a p-type semiconductor. For example, a dopant of Group II, such as In, B, or Ga, may be utilized to produce

the p-type material. To light up a phosphor screen of a display device, a forward bias voltage is applied across the junction so that electrons flow from the substrate into the SBCF region. Due to the NEA property of this region, many electrons immediately escape to the vacuum level and head toward the phosphor screen anode plate placed above this diode structure, and hence light it up for display. To turn off the phosphor screen, one simply switches off the applied voltage across the junction.

Figure 1 schematically illustrates an embodiment of the junction-based field emission structure of the present invention. As shown, the structure comprises a junction generally indicated at 10, and composed of a substrate 11, which may be composed of metal, such as Al, Au, Pt, or Cu, or an n-type semiconductor (n-Si), and on which is deposited an SBCF 12, which film may be composed of silicon, oxygen, and CS, or another suitable alkali metal. The substrate 11 with deposited SBCF 12 (junction 10) is located in a vacuum case 13, and in spaced relation to a positively biased phosphor screen anode plate 14, plate 14 being positively biased by a power supply 15 connected intermediate the plate 14 and ground indicated at 16 by electrical leads 15' and 16'. A power supply 17 is connected between the substrate 11 and ground 16 and a power supply 18 is connected between the SBCF 12, via a switch 19, and ground 16 by electrical leads 20, 21, and 22, to produce a small forward bias voltage across the junction 10 so that electron transport is from the substrate 11 into SBCF region 12. Upon entering this NEA region 12, electrons are released into the vacuum case 13 and accelerated toward the positively biased phosphor screen anode plate 14, hence lighting it up for display. To turn off the phosphor

screen, simply move the blade of switch 19 from the closed (solid line) position to an open (dash line) position.

By way of example, the substrate 11 may have a thickness of many micrometers to many millimeters, with the SBCF 12 having a thickness of a few micrometers down to 100 nanometers, the positive bias on the anode plate is in the range of 500 V to 5 KV, and the small forward bias voltage applied across the junction 10 is in the range of 0.5 to 5 volts, with the vacuum case 13 being at a pressure of 10^{-5} to 10^{-7} Torr, and with the phosphor screen anode plate 13 being located from the SBCF surface by a distance of less than 1 micrometer to about 20 micrometers.

Figure 2 schematically illustrates a multiple junction-based field emission structure generally indicated at 30 composed of a substrate 31 of n-Si, and on one side of which is deposited a metal contact 32 to n-Si (Al or lower work function material to form an ohmic contact). A plurality of p-Si contacts 33 are formed in an opposite surface of substrate 31 and a layer 34 of SiO₂ having a thickness of >2 μm , as indicated by arrow 2, is deposited on that opposite side with openings 35 therein to expose the p-Si contacts or pads 33. In spaced relation to the substrate 31, a positively biased phosphor screen anode plate 36 is located, with plate 36 being positively biased by a power supply 37 connected intermediate plate 36 and ground indicated at 37. A power supply 38 is connected between the metal contact 32 and ground 37, and a power supply 39 is connected between p-Si contacts or pads 33 via a switch 40 and ground 37 to produce a small forward bias voltage across the junctions so that electron transport is from the substrate 31 into the p-Si contacts 33, and Si/Cs/O nanoclusters indicated at 41 are released into a vacuum case 42 and accelerated toward the positively

biased phosphor screen anode plate 36. To turn off the phosphor screen, simply move the blade of switch 40 from the closed (solid line) position to an open (dash line) position.

Addressable and multiple junction-based field emission structures for display can be developed upon this primary single junction-based field emission structure of Figure 1 by laying down an insulating layer on top of a properly marked substrate, followed by removing the mark and then depositing an SBCF. For an SBCF with a small band gap, a small bias voltage on the order of half the band gap is sufficient to turn on this junction-based field emitter. With such low turn-on voltage, the junction-based field emission structure of the present invention promises field emission flat panel displays with much lower turn-on voltages, low energy consumption, and therefore much simpler (and less expensive) power supplies than conventional structure. Because of its simpler geometry, there are fewer and easier manufacturing steps associated with the fabrication of addressable segments of cathode material suitable for incorporation in a flat panel display. Simpler manufacturing processes associated with this diode structure translate directly to lower costs, especially when compared to conventional gated tip (triode) arrays.

It has thus been shown that the present invention provides a junction-based field emission structure that eliminates the problems associated with sharp tip field emission structures, and the junction-based approach is simpler and less expensive to manufacture. The substrate of the junction-based structure may be a metal, an n-type material, or a doped p-type material, with the SBCF being composed of silicon, oxygen, and an alkali metal, which can be deposited on the substrate by known deposition techniques. In

addition, the junction-based structure has a low turn-on voltage and low energy consumption.

5 While particular embodiments, along with specific materials, parameters, etc., have been set forth to exemplify and teach the principles of the invention, such are not intended to be limiting. Modifications and changes may become apparent to those skilled in the art, and it is intended that the invention be limited only by the scope of the appended claims.

THE INVENTION CLAIMED IS

1. In a field emission display, the improvement comprising:

a junction-based field emission structure.

2. The improvement of Claim 1, wherein said junction-based field emission structure includes a substrate, and a film of SBC deposited on the substrate.

3. The improvement of Claim 2, wherein said substrate is composed of materials selected from the group consisting of metals and n-type semiconductors.

4. The improvement of Claim 2, wherein said SBC is composed of silicon, oxygen, and an alkali metal.

5. The improvement of Claim 4, wherein said alkali metal is selected from the group consisting of Cs, Ba, K, Rd, and Li.

6. The improvement of Claim 1, wherein said junction-based field emission structure is connected to a power source for producing a forward bias voltage thereacross.

7. The field emission display of Claim 1, wherein said junction-based field emission structure is located in a vacuum case and in spaced relation to a positively biased phosphor screen anode plate, and said junction-based field emission structure is operatively connected to a power supply for producing a forward bias voltage there across.

8. The field emission display of Claim 7 additionally includes a switch for shutting off applied electrical potential across said junction-based field emission structure.

9. The improvement of Claim 1, wherein said junction-based field emission structure includes an n-Si substrate, a metal contact on one side of said substrate, a plurality of p-Si contacts in a surface of an opposite side of said substrate, and a layer of insulation on said opposite side of said substrate having openings therein which expose said plurality of p-Si contacts.

10. A junction-based field emission display, comprising:
a vacuum case,
a phosphor screen anode plate positioned in said vacuum case,
means for applying a bias voltage on said anode plate,
a junction-based field emission structure positioned in said vacuum case and spaced from said anode plate,
means for applying a bias voltage across the junction-based field emission structure, and means for cutting off the bias voltage across the junction-based field emission structure.

11. The display of Claim 10, wherein the bias voltage on said anode plate is positive.

12. The display of Claim 10, wherein said junction-based field emission structure comprises a substrate and a layer of SBC.

13. The display of Claim 12, wherein said bias voltage across the junction-based field emission structure is a forward bias voltage, whereby electron transport is from the substrate into the SBC layer, and electrons are released from said layer into said vacuum case and are accelerated toward said phosphor screen anode plate.

14. The display of Claim 12, wherein said substrate is composed of material selected from the group consisting of metals and n-type semiconductors.

15. The display of Claim 12, wherein said layer of SBC is composed of silicon, oxygen, and an alkali metal.

16. The display of Claim 15, wherein said alkali metal is selected from the group consisting of Cs, Ba, K, Rb, Li, and other alkali metals.

17. The display of Claim 12, wherein said layer of SBC has a thickness in the range of a few micrometers down to 100 nanometers.

18. The display of Claim 13, wherein the forward bias voltage is in the range of 0.5 to 5 volts.

19. The display of Claim 12, wherein the layer of SBC comprises a small band gap, low work function, NEA material.

20. The display of Claim 19, wherein the bias voltage across the layer of SBC is on the order of half the band gap.

21. The display of Claim 9, wherein said junction-based field emission structure comprises a substrate, a layer of metal on one side of said substrate and a layer of insulation on the opposite side of said substrate, and a plurality of p-Si contacts in the opposite surface of said substrate.

22. The display of Claim 21, wherein said substrate is composed of n-Si, wherein said layer of metal is composed of Al, and wherein said layer of insulation is composed of SiO₂.

23. The display of Claim 21, wherein said plurality of p-Si contacts includes a dopant of Group II materials, including In, B, and Ga.

1/1




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/14799

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H01J1/30 H01J31/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 06135 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 12 February 1998 (1998-02-12) claims 1-10	1-3,7, 10-14
X	A.D. COPE ET AL.: "SCANNING BEAM PERFORMANCE FROM A NEGATIVE-ELECTRON -AFFINITY ACTIVATED SILICON COLD CATHODE" RCA REVIEW , vol. 34, September 1973 (1973-09), pages 408-428, XP002116867 page 408-428	1
X	US 4 506 284 A (SHANNON JOHN M) 19 March 1985 (1985-03-19) claims 1-9	1
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 September 1999

Date of mailing of the international search report

13/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van den Bulcke, E

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/14799

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 30 35 988 A (SIEMENS AG) 29 April 1982 (1982-04-29) claims 1-7 ---	1
A	BE 679 967 A (N.V. PHILIPS' GLOEILAMPENFABRIEKEN) 24 October 1966 (1966-10-24) claims 1-3 ---	1
A	KOHN E S: "THE SILICON COLD CATHODE" , IEEE TRANSACTIONS ON ELECTRON DEVICES, VOL. 20, NR. 3, PAGE(S) 321 - 329 XP002006374 ISSN: 0018-9383 page 328 ---	1
A	ELLIOTT S. KOHN : "COLD-CATHODE ELECTRON EMISSION FROM SILICON" APPLIED PHYSICS LETTERS, vol. 18, no. 7, 1 April 1971 (1971-04-01), pages 272-273, XP002116868 ---	
A	EP 0 287 067 A (CANON KK) 19 October 1988 (1988-10-19) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/14799

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9806135 A	12-02-1998	EP 0858673 A	19-08-1998
US 4506284 A	19-03-1985	GB 2109160 A	25-05-1983
		CA 1201818 A	11-03-1986
		DE 3240441 A	19-05-1983
		ES 517118 A	01-01-1984
		FR 2516307 A	13-05-1983
		HK 19386 A	27-03-1986
		IT 1153005 B	14-01-1987
		JP 3041931 B	25-06-1991
		JP 58087733 A	25-05-1983
		NL 8204240 A	01-06-1983
DE 3035988 A	29-04-1982	NONE	
BE 679967 A	24-10-1966	NL 6505085 A	24-10-1966
		CA 923960 A	03-04-1973
		DE 1564401 A	02-10-1969
		FR 1477155 A	30-06-1967
		GB 1147883 A	
		JP 49009255 B	02-03-1974
		SE 312382 B	14-07-1969
EP 0287067 A	19-10-1988	JP 2612572 B	21-05-1997
		JP 63257158 A	25-10-1988
		DE 3851080 D	22-09-1994
		DE 3851080 T	22-12-1994
		US 4833507 A	23-05-1989

THIS PAGE BLANK (USPTO)